

genechecker UF-300 Real-time PCR System




Fast, Compact and Intuitive Platform for Point-of-care Molecular Diagnostics

- Patented chip based reaction provides rapid output- "40 Cycles in 20 Minutes".
- Intuitive user interface (LCD touch panel) makes the test simple and easy.
- Small footprint of the platform makes it ideal for point-of-care testing applications.
- DC driven operation with low power consumption (Battery operation is possible.)
- Improved temperature accuracy and uniformity to meet the requirements in diagnostics.
- The model with dual detection channels (FAM/ROX) is available.

Innovative platform to make your PCR diagnostics faster

Long turn around time of PCR test and its bulky and heavy instrumentation have been the key factors limiting the spread of this highly precise and sensitive detection method in point-of-care diagnostic applications. Genesystem invented a microfluidic chip based PCR method associated with compact and sophisticated hardware mechanism which dramatically reduces the TAT of PCR testing down under 20 minutes. **genechecker** platforms adopted proprietary polymer chip (Rapi:chip™) which enables even faster thermal treatment of the samples in it than the case of using PCR tubes at conventional PCR instruments. The thermal cycling mechanism of **genechecker** achieves 8°C/sec ramping rate for both heating and cooling. The unique test format and State-of-the-art hardware technology of **genechecker** platform makes the PCR tests faster than ever.




Integrated touch panel user interface for intuitive controls

genechecker UF-300 real-time PCR system has touch panel interface on the top so that users can intuitively set the parameters and instantly run the tests. This 8 inch sized panel is made of TFT display to provide brighter view and faster response.

Improved instrument performance for delicate diagnostic application

While it maintains its unique performances of ultra-fast reactions, **genechecker** UF-300 real-time PCR system offers improved temperature accuracy and uniformity. This platform has dual detection channels (FAM/ROX) for the application demanding internal controls of the test.

INTUITIVE USER INTERFACE MAKES THE TEST SIMPLE AND EASY



Main screen consists of four simple menu which can be intuitively chosen and used.

Test protocols can be intuitively programmed and easily reviewed by user.

For easy analysis, real-time reaction curves are displayed as the same format of other real-time PCR instruments.

SPECIFICATION

- Operating Mechanism	Precise control of peltier element
- Temperature Accuracy	± 0.2°C
- Temperature Uniformity	± 0.2°C (well to well)
- Ramping Rate	8°C / second
- Range of Temperature Setting	1 ~ 99°C (0.1°C resolution)
- Sample Format	Polymer based 3-dimensional microfluidic chip
- Number of Sample per Run	10
- Reaction Volume	10 µl
- Method of Detection	Measurement of fluorescence signal using CMOS module
- Display and User Interface	7 inch TFT display capacitive touch panel
- Type of Excitation	High brightness LED
- Detection Channel	FAM and ROX
- Emission Wavelength	FAM : 472 nm / ROX : 570nm
- Power	AC 100-240V (50-60Hz) Input / DC 12V Output(70W)
- Current Consumption	Max. 2.0A
- Connectors	USB Type A 2 ports
- Dimension	218(w) x 200(d) x 142(h) mm
- Weight	3.3 kg

ORDERING INFORMATION

Catalog No.	Product	Pack Size
1399100200	genechecker UF-300 Real-time PCR System	1 SET
1699100500	Optional Power Cable for Car Cigarette Power Socket	1 SET
9699100100	Rapichip™ 10-well PCR Chip (S-Pack) Standard Pack (48pcs/PK)	48 pcs / PK
9699100101	Rapichip™ 10-well PCR Chip (M-Pack) Medium Pack - 8PK of Standard Pack	384 pcs / PK
9699100102	Rapichip™ 10-well PCR Chip (L-Pack) Large Pack - 16PK of Standard Pack	768 pcs / PK

Genesystem Co., Ltd.